

FABRIC POSTCARDS

Materials:

Pellon Peltex 72 or Dritz InnerFuse double-sided stiff interfacing cut to 4"x6" (or slightly larger)

Fabric scraps and trims; Fabric lights (for address side of card)

Ironing board, iron and pressing cloth

Scissors

Rotary cutter and mat (for trimming), 6 1/2" square ruler

Sewing machine that will zigzag, open toed foot

Thread: 100% cotton size 50 for piecing, fancy threads for embellishment

Permanent ink pen: Gelly Roll medium pen by Sakura or calligraphy pigma pen

Glue for adhering embellishments: E6000 by Eclectic Products or Fabri-Tac

FUSING THE PIECES AND FINISHING

Finish your top design. Center it on the Peltex with the solid piece on the bottom.

Fuse the three pieces together with a hot dry iron. You may want to use a pressing cloth.

Trim to 4"x6" or slightly less. Stitch outside edge with overcast stitch, zig zag, or satin stitch.

Glue on any final embellishments.

MAILING THE POSTCARDS

If you have added embellishments you may wish to have the cards hand-cancelled.

First class postcards must be no smaller than 3 1/2" x 5" x 0.0007" thick; no larger than 4 1/2" x 6" x 0.016" thick. You can get clear envelopes from clearenvelopes.com if you wish. Order size B4X6.